



### RETAIL ELECTRIC/CRAFT KILN/FURNACE

VALID FROM 01/08/2021

FRONT LOADER MODEL	INTERNAL W x D x H / mm	Ft <sup>3</sup>	L <sup>3</sup>	KG	Programmer Fittings (GST included)	SR92 (GST included)	STAFFORD (GST included)
<b>Small Kiln</b>							
K2 FL	230 x 230 x 230	0.40	12	30	\$ 4,638	\$ 5,223	\$ 5,808
K4 FL	330 x 330 x 230	0.90	25	55	\$ 5,398	\$ 5,980	\$ 6,565
K4A FL	330 x 330 x 330	1.40	35	75	\$ 5,879	\$ 6,464	\$ 7,049
K6 FL	380 x 380 x 460	2.35	66	95	\$ 7,011	\$ 7,596	\$ 8,181
<b>Large Kiln</b>							
K7MW FL	460 x 460 x 460	3.40	97	175	\$ 10,812	\$11,397	\$ 11,982
K8B FL	460 x 460 x 686	5.06	145	380	\$ 12,363	\$12,948	\$ 13,533
K9 FL	460 x 460 x 915	6.80	193	460	\$ 13,371	\$13,956	\$14,541
K10 FL	610 x 610 x 610	8.00	226	440	\$ 14,380	\$14,965	\$15,550
K11A FL	610 x 610 x 760	10.00	283	500	\$ 16,458	\$17,043	\$17,628
K12 FL	610 x 610 x 915	12.00	340	520	\$ 17,606	\$18,191	\$18,776
K12A FL	610 x 610 x 1370	18.00	510	580	\$ 21,267	\$22,117	\$22,967
K13 FL	610 x 610 x 1830	24.00	680	650	\$ 23,380	\$24,230	\$25,080
<b>TOP LOADER MODEL</b>							
TOP LOADER MODEL	INTERNAL W x D x H / mm	Ft <sup>3</sup>	L <sup>3</sup>	KG	Programmer Fittings (GST included)	SR92 (GST included)	STAFFORD (GST included)
<b>Small Kiln</b>							
K5 TL	345 x 345 x 370	1.53	44	85	\$ 6,970	\$ 7,555	\$ 8,140
K6 TL	380 x 380 x 460	2.35	66	95	\$ 8,230	\$ 8,815	\$ 9,400
<b>Large Kiln</b>							
K7 TL	460 x 460 x 460	3.40	97	300	\$ 11,890	\$ 12,475	\$ 13,060
K8 TL	460 x 460 x 610	4.50	129	410	\$ 12,400	\$ 12,985	\$ 13,570
K9 TL	915 x 460 x 460	6.80	193	460	\$ 13,960	\$ 14,545	\$ 15,130
K10 TL	610 x 610 x 610	8.00	226	500	\$ 14,660	\$ 15,245	\$ 15,830
K11 TL	915 x 460 x 610	9.00	256	520	\$ 15,720	\$ 16,305	\$ 16,890
K12 TL	915 x 610 x 610	12.00	340	560	\$ 16,760	\$ 17,345	\$ 17,930





**NOTE: ALL UNITS CONNECT WITH NEUTRAL**

MODEL	PHASE	VOLTS	AMPS	KW	TEMP°C
K2 FL	1	240	10	2.4	1200°C
K2 FL	1	240	15	3.6	1280°C
K4 FL	1	240	10	2.4	1100°C
K4 FL	1	240	15	3.6	1280°C
K4A FL	1	240	10	2.4	1100°C
K4A FL	1	240	15	3.6	1280°C
K5 TL	1	240	15	3.6	1280°C
K6 FL/TL	1	240	20	4.8	1100°C
K6 FL	1	240	25	6.0	1280°C
K6 TL	2	415	12.5	6.0	1280°C
K7 MW FL	1	240	30	7.2	1280°C
K7 MW FL	2	415	15	7.2	1280°C
K7 MW FL	3	415	10	7.2	1280°C
K7 TL	3	415	10	7.2	1280°C
K8 TL	3	415	15	10.8	1280°C
K8B FL	3	415	15	10.8	1280°C
K9 FL/TL	3	415	20	14.4	1280°C
K10 FL/TL	3	415	23	16.5	1280°C
K11 TL	3	415	25	18	1280°C
K11A FL	3	415	25	18	1280°C
K12 FL/TL	3	415	28	20.16	1280°C
K12A FL	3	415	40	28.8	1280°C
K13 FL	3	415	50	36	1280°C

Please note: For extensive 1280°C/stoneware, we can supply K6 as 240V-25amp, for extended operating life of elements, requires direct wiring or 30 amp plug top and lead (not supplied).

It is recommended that circuit breakers or fuses are electrical cables are rated at a minimum of 20% above the required amperage of the unit.

Three phase kilns are 5 wire – 1 earth, 1 neutral, 3 actives.

Note: We can manufacture quite a number of 2 and 3 phase kilns as single phase if you have adequate single phase power available. The same may also be done with the multi-sided octagonal kilns.